




Role of Modeling in the Remediation of the WP14/LF15 Chlorinated Solvent Plume at Dover Air Force Base, Delaware

2019 Federal Remediation Technologies Round Table | May 22 | Reston, Virginia



Presented By:

Scott Morgan, PG

AECOM, Newark, DE, USA

Role of Modeling in the Remediation of the WP14/LF15 Chlorinated Solvent Plume at Dover Air Force Base, Delaware

- Introduction
- Location and Background
- Fate and Transport Modeling
- Source Delineation and Treatment
- Summary and Path Forward




Introduction

This is a case study of the use of various modeling and data evaluation tools to manage and investigate environmentally impacted sites.

Two locations at Dover Air Force Base, WP14/LF15 were selected as our case study to show how multiple modeling tools were employed at various points during a nearly 30-year long project.

Models developed across the base and refined to address issues specifically at WP14/LF15 provided greater assurance for implemented and augmented remedial technologies to reach Remedial Action Objectives.


Location of WP14 and LF15



Background of WP14 and LF15


- WP14 – Liquid Waste Disposal Pit
 - Active in late 1950s to early 1960s
 - Disposed of liquid shop wastes including oils and solvents
- LF15 – Landfill
 - Active during the 1960s
 - Used for solid waste and small quantities of shop wastes
- Early 1960s (precise time frame unknown), sites were covered with soil and grass. No active remediation was conducted.
- Environmental investigations revealed a groundwater contamination plume, primarily PCE and TCE and their breakdown products.
- Monitored natural attenuation was implemented per 1997 Record of Decision.

Environmental Restoration Time-Line



* Published in 1998
 ** Published in 2000
 *** Published in 2001

Plume over Time




Legend




- Site Boundary
- ⊕ Monitoring Well

- >5µg/L Total Solvent Concentration Contour
- >500µg/L Total Solvent Concentration Contour



Trend Evaluation of MNA for meeting RAOs




Simulated PCE Plume Assuming no Source Area



T = Present (1994), source removed




T = Source removed + 10 years



T = Source removed + 20 years



T = Source removed + 30 years




Fate and Transport Modeling


- Graphical trend analysis has been used for plume monitoring since 2003.
- More robust numerical modeling was performed, starting in 2013, to provide information on the fate and transport of COCs and time to reach RAOs.
- Site data were used to calculate site-specific degradation rates. Degradation rates were refined through iterative model runs to best fit observed constituent distributions using both reactive (RT3D) and non-reactive (MT3DMS) model codes.
- At WP14/LF15, graphs of COC trends in source area wells were used to predict when source area concentrations would fall below RAOs.
- Model runs with calibrated parameters and assuming no continuing source were used to estimate when the dissolved plume areas would fall below RAOs.
- Modeling indicated that total time to reach RAOs 40+ years.

Source Delineation and Treatment



- 77 locations across WP14 and LF15
- Evidence of previously unknown source material
- Highest PCE Concentration = 29,822 µg/L
- Carbon injections in AAB treatment area in 2015



Source Area Well Trend Graph



Updated Simulated Concentrations over Time



Simulated concentrations drop below RAOs in approximately 20 to 25 years



Summary

- WP14/LF15 was selected as our case study to show how multiple modeling tools were employed at various points during a nearly 30-year long project.
 - Early on, USGS models provided foundational understanding of F&T and support of remedy selection.
- Previous modeling exercises at modeling studies at DAFB indicated the importance of understanding source area conditions for overall plume persistence.
- Concentration trends inconsistent with model results raised concerns that RAOs would not be met in reasonable time frame and that source area conditions may be different than expected at WP14/LF15.
- Subsequent source area investigation identified mass remaining in source area which was treated using
- Refined 3D Fate and Transport modeling and Trend analysis supported a change to the existing remedy.

Path Forward

- Continue annual plume monitoring and evaluation of concentration trends as compared to predicted changes.
- Enhance the Conceptual Site Model through Environmental Sequence Stratigraphy (ESS)
- When RAOs are reached, use statistical analysis or modeling to demonstrate sustainable achievement of RAOs



U.S. AIR FORCE CIVIL
ENGINEER CENTER



DOVER AIR FORCE
BASE

AECOM

Imagine it.
Delivered.

Thank You!

Scott Morgan, PG
AECOM, Newark, DE, USA
T 302.781.5935
E scott.a.morgan@aecom.com